

cinema of dreams



SEACAM *silver* – NIKON D700

www.seacam.com

Features

The SEACAM silver for the NIKON D700 sets new standards in design and ergonomics. Due to the special construction, the mounting of the camera is especially easy.

The housing is milled out of a saltwater-proof light metal alloy twice hardened and high-value anodized

Special longevity is achieved through use of materials of only the best quality: stainless steel, anodized aluminum, premium synthetics as well as Helicoil threads.

Double sealing with seamless, high-quality precision O-rings protects all shafts and press buttons. The main O-ring is of a particularly strong dimension.

The titanium SAFETY LOCK fastening system safely secures both housing shells.

Our interchangeable viewfinder system includes 4 different viewfinders and can be exchanged without any tool.

The easy mounting system and the double O-ring sealing particularly secures the SEACAM front port connection with its bayonet thread.



Functions

Turning knobs and control levers

Main switch, LCD light, shutter release, front / rear dial, manual focus, zoom, C-S-M focus select, +/- compensation, mode, flash +/- compensation, AF-area control, AE-L / AF-L or AF-ON, play, delete, lens release.

Push buttons

Multi selector, quality, white balance, ISO, menu, protection, index, zoom, OK, info.

Data

Clearly laid out LCD color monitor window and tilted anti-glare upper display window.

2 flash sockets N5 or S6, 2 flash arm tees 25 mm, tripod thread 3/8", M8 thread on the housing roof, 2 removable handles and optic-acoustical water alarm.

Remote socket optional

Spare O-ring set, lubricant, hex-wrench set and locking strap in neoprene bag; protection caps and instruction manual.

Dimensions (W x H x D): 260 x 190 x 130 mm excluding port, viewfinder and handles.

Weight: 2750 g excluding port and viewfinder, neutral under water depending on port and viewfinder.

Operation depth: – 80 m, deeper operation depth on request.